

CPS Small 9W LED

Coughtrie

Custodial

Infrastructure

Social Housing

One of our most popular social housing fittings. Anti-vandal circular surface mounted bulkhead. Available with emergency and a selection of detector options. This fitting can be found in applications ranging from tower blocks to closes. Anywhere vandalism is a challenge, the CPS has proven to stand the test of time.

Applications

- Underpasses
- Stairwells
- Car Parks
- Prison circulation areas
- Police stations
- Detention centres
- Schools
- Corridors
- Indoor sports applications



Features

- Die-cast aluminium base
- Clear or opal prismatic UV stabilised fire retardant polycarbonate diffuser
- SA770 low smoke low toxicity silicone elastomer
- IP65
- IK10++

Options


- Black, Grey or White
- Integrated 3hr emergency & optional self-test
- Digital Dimmable Ballast
- Microwave
- Dusk to Dawn
- Security screws included for added vandal resistance *

*Supplied in a separate bag. Security screwdriver WS7115 required.


CE BS.EN60598-2-1 IP65

Technical Specifications

LUMINAIRE CHARACTERISTICS	
LEDs	Tridonic CLE G4
DRIVER	Constant current
WORKING TEMP	-25°C to 50°C
EMERGENCY WORKING TEMP	-5°C to 50°C
SYSTEM LUMENS	1050lm
EFFICACY	118lm/W
CRI	>80
CCT	4000K
LIFETIME	50,000hrs
IP RATING	IP65
IK RATING	IK10++
ELECTRICAL CHARACTERISTICS	
POWER	8.9W
VOLTAGE	24.2 – 27.5V
CURRENT	350mA



Photometric Data



Sample Order Code

CPS-9LED	+	EMG	+	DD	/	B	/	CL (SMALL)
Luminaire		Emergency		Sensor		Finish		Diffuser
CPS		Emergency = EMG		Dusk to Dawn = DD Corridor Function = CF CF+Daylight Monitoring = CFDM Microwave = MWD		Black = B Grey = G White = W		Opal = OP Clear = CL

CPS-9LED+EMG+DD/B/CL (SMALL) = 9WLED, Emergency, Dusk to Dawn, Black, Clear Diffuser