

Coughtrie



# FIRE RATED DOWNLIGHTS

## LS RANGE

**Fixed Downlight**  
LSF



**Adjustable Single Ring**  
LSA1



**Adjustable Double Ring**  
LSA2



**Fixed Darklight**  
LSFD



**Adjustable Darklight**  
LSA1D



**Rotational**  
LSAR



## Product Specifications

- 2700K, 3100K & 4000K
- 105 lumens per watt
- 80 Ra (90 & 95 Ra available to order)
- Dimmable
- Casambi enabled
- 3 Step MacAdam
- Powder coated matt white finish
- Stainless steel, chrome & copper finish to special order
- Darklight inner black finish (optional white)
- Low profile bezel
- Fire rated
- 40° standard beam (20° & 60° available to order)
- Frosted or clear glass
- 50,000 hour life
- Satisfies Building Reg. Part L 1&2

## Sample Order Code

PRODUCT RANGE	ADJUSTABLE OR FIXED	PRODUCT TYPE	WATTS (W)	KELVIN(K)	BEAM ANGLE	FINISH COLOUR	GLASS TYPE
LS	F = Fixed A1 = Adj 1 A2 = Adj 2 R = Rotation	D = Darklight If Not = Blank	9W	2700 3100 4000	20 40 60	SS = Stainless Steel CH = Chrome W = White C = Copper	C = Clear F = Frosted
<b>LS</b>	<b>A1</b>	<b>D</b>	<b>9W</b>	<b>3100K</b>	<b>40</b>	<b>W</b>	<b>F</b>

**LSA1D-9W3100K40-WF** = LS range, single ring, adjustable darklight, 9w, 3100k, 40° beam angle, white finish, frosted glass